

# Test report

## Nordpeis X-25F

NS-EN 13229 Inset appliances including open fires fired by solid fuel –  
Requirements and test methods

**KEYWORDS**  
Enclosed wood heater  
NS-EN 13229  
Inset appliance  
Safety

**VERSION**

1

**DATE**

2013-02-15

**AUTHOR(S)**

Herbjørg M. Ishol

**CLIENT(S)**

Nordpeis AS

**CLIENT'S REF.**

Ola Gjone

**PROJECT NO.**

102044.35

**NUMBER OF  
PAGES/APPENDICES**

8 incl. 3 appendices

**TEST OBJECT**

Enclosed wood heater

**TEST OBJECT RECEIVED**

2013-01-21

**TEST PROGRAM**

Safety acc. to EN 13229

**TEST LOCATION**

Trondheim

**DATE OF TEST**

2013-01-25

**ABSTRACT**

The Nordpeis X-25F has been subjected to safety testing according to EN 13229.

The distances from brick wall shall be minimum 15 mm to the side and 15 mm to the back with shielded or insulated flue pipe.

The distance from top of casing to the ceiling shall be minimum 400 mm. The convection area of the casing has to be minimum 300 cm<sup>2</sup> at the inlet and 450 cm<sup>2</sup> at the outlet.

The stove has to be delivered with glove.

The test results relate only to the items tested

**PREPARED BY**

Herbjørg M. Ishol

SIGNATURE



**APPROVED BY**

Asbjørn Østnor

SIGNATURE



**REPORT NO.**

102044.35B

CLASSIFICATION

Restricted