



Rhein-Ruhr Feuerstätten Prüfstelle

**Rhein-Ruhr Feuerstätten Prüfstelle • Im Lipperfeld 34 b • 46047 Oberhausen**

- ❖ State recognized testing laboratory, registered No. NRW 15 in accordance with construction supervision directives
- ❖ Recognized testing laboratory in construction supervision licensing procedures
- ❖ Recognized DIN CERTCO testing laboratory, registered No. PL 139
- ❖ European Commission recognized testing laboratory, notified body number: 1625

## Test report No. RRF – 50 11 2758

**Testing method:** Test according to DIN EN 15250:2007, the certification program *DINplus* and its amendment according to Art. 15a B-VG of the Republic of Austria

**Fulfilled requirements:** BStV of the City of Munich, the City of Regensburg and the City of Stuttgart, FBStVO of the City of Aachen, 1. and 2. level of 1. BImSchV of Germany and LRV of Switzerland.

**Manufacturer:** **Nordpeis AS**, Gjellebekkstubben 9/11, 3420 Lierskogen, Norway

**Tested product:** Slow heat release appliance **Salzburg M**

**Type:** Double allocation is not acceptable.

**Rate of heat release:** 141945 kJ

**Test result:** The CO content of the flue gases emitted by the above-mentioned fireplace – at nominal heating capacity and under the testing conditions stipulated by the DIN EN 13240, using wood logs as fuel – is 0,095 Vol.-%, referring to 13 % O<sub>2</sub> (equal to 1188 mg/m<sup>3</sup>).

The dust-like emissions in the flue gas – under the conditions described above – are 32 mg/m<sup>3</sup>, the NO<sub>x</sub>-content is 142 mg/m<sup>3</sup>, the C<sub>n</sub>H<sub>m</sub>-content is 77 mg/m<sup>3</sup>, for wood logs referring to 13 % O<sub>2</sub>.

Under the conditions described above, the level of efficiency is 84,0 %.

**Head of Testing Laboratory**

**Dipl.-Ing. Rosenfeld**  
Oberhausen, 13.09.2011